RESILIENT TILE FLOORING - QUIETLOK® CONTINENTAL

COLLECTION/PATTERN: BASIN

PRODUCT ID: QLC-BSN-20H-5.0

QUIETLOK

TECHNICAL SPECIFICATIONS

SIZE	9.56” x 60” (242mm x 1524mm)
WEAR LAYER THICKNESS	20MIL (0.5mm)
OVERALL THICKNESS	5.0mm (0.20”)
CORE THICKNESS	4.0mm (0.16”)
CORE MATERIAL	SPC RIGID CORE
PAD	1mm (0.04”) IXPE FOAM PAD
EDGE DETAIL	MICRO-BEVEL
EMBOSSING	DEEP OVERALL EMBOSSING
FINISHING	3-LAYER CERAMIC BEAD UV COATING
COVERAGE/CARTON	8 PIECES (31.89 sq.ft)
COVERAGE/PALLET	48 CARTONS (1,530.72sq.ft)
COVERAGE/CONTAINER	16 PALLETS (24,491.52 sq.ft)
LIMITED WARRANTY	20 YEAR COMMERCIAL
RATINGS	STC 62 & IIC 69

PRODUCT COMPONENTS

floor score

CERTIFIED BY SCS Global Services

GREENGUARD GOLD

1 DURABLE WEAR LAYER
- 3-LAYER SCRATCH RESISTANT UV COATING
- 20-MIL CLEAR WEAR LAYER

2 VINYL DECOR LAYER

3 2G CLICK SYSTEM
- LOCKS ON BOTH LONG & SHORT SIDES

4 SPC RIGID CORE
- INCREASED DENSITY
- MORE DIMENSIONAL STABILITY

5 IXPE FOAM PAD
- HIDES SUBFLOOR IMPERFECTIONS
- REDUCES DEFLECTION
- DECREASES SOUND TRANSMISSION

MGROUP

OFFICE: 706.350.4300 | INFO@QUIETLOK.COM
WWW.MGROUPCORP.COM/QUIETLOK/

REV. DATE - 04/2025