

RESILIENT TILE FLOORING - QUIETLOK® CONTINENTAL

COLLECTION/PATTERN: UMBER

PRODUCT ID: QLC-UMB-12H-5.0


QUIETLOK®

TECHNICAL SPECIFICATIONS

SIZE	9.56" x 60" (242mm x 1524mm)
WEAR LAYER THICKNESS	12MIL (0.3mm)
OVERALL THICKNESS	5.0mm (0.20")
CORE THICKNESS	4.0mm (0.16")
CORE MATERIAL	SPC RIGID CORE
PAD	1mm (0.04") IXPE FOAM PAD
EDGE DETAIL	MICRO-BEVEL
EMBOSSING	DEEP OVERALL EMBOSSING
FINISHING	3-LAYER CERAMIC BEAD UV COATING
COVERAGE/CARTON	8 PIECES (31.89 sq.ft)
COVERAGE/PALLET	48 CARTONS (1,530.72sq.ft)
COVERAGE/CONTAINER	16 PALLETS (24,491.52 sq.ft)
LIMITED WARRANTY	15 YEAR COMMERCIAL
RATINGS	STC 51 & IIC 54



PRODUCT COMPONENTS



1 DURABLE WEAR LAYER

- 3-LAYER SCRATCH RESISTANT UV COATING
- 12-MIL CLEAR WEAR LAYER

2 VINYL DECOR LAYER

2G CLICK SYSTEM

- LOCKS ON BOTH LONG & SHORT SIDES

SPC RIGID CORE

- INCREASED DENSITY
- MORE DIMENSIONAL STABILITY

IXPE FOAM PAD

- HIDES SUBFLOOR IMPERFECTIONS
- REDUCES DEFLECTION
- DECREASES SOUND TRANSMISSION

MGROUP™

OFFICE: 706.350.4300 | INFO@QUIETLOK.COM
WWW.MGROUPCORP.COM/QUIETLOK/

REV. DATE - 04/2025

