

RIGID CORE FLOORING - QUIETLOK® ALPINE

COLLECTION/PATTERN: HEATHERED BISQUE 60

PRODUCT ID: QLREWGC20CRSY--60

QUIETLOK®


SAMPLE IMAGE



CERTIFICATIONS



INSTALLATION



NOTES

HIGH COMPRESSION RATING FOR MAXIMUM DURABILITY
DOES NOT TELEGRAPH MOST SUBFLOOR IMPERFECTIONS
ADDITIONAL LIMITED WARRANTY AVAILABLE ON A CASE BY CASE BASIS

TECHNICAL SPECIFICATIONS

SIZE	230.12mm x 1524mm (9.06" x 60")
WEAR LAYER THICKNESS	20MIL
OVERALL THICKNESS	5mm
CORE MATERIAL	STONE PLASTIC COMPOSITE
UNDERLAYMENT	1mm ANTI-MICROBIAL HIGH DENSITY IXPE
EDGE DETAIL	MICRO-BEVELED
FINISH	MINERAL ENHANCED UV COATING
EMBOSSING	ALL OVER
SQ. FT./CARTON	26.41 (2.45m ²)
LIMITED WARRANTY	15 YEARS LIGHT COMMERCIAL, 5 YEARS COMMERCIAL
RATINGS	STC 62 & IIC 68

MGROUP

OFFICE: 706.350.4300 | INFO@QUIETLOK.COM
WWW.MGROUPCORP.COM/QUIETLOK/

