RIGID CORE FLOORING - QUIETLOK® ALPINE

COLLECTION/PATTERN: HEATHERED PARCHMENT 60

PRODUCT ID:

QLREWGC20CRAG--60




SAMPLE IMAGE



CERTIFICATIONS



INSTALLATION



NOTES

HIGH COMPRESSION RATING FOR MAXIMUM DURABILITY

DOES NOT TELEGRAPH MOST SUBFLOOR IMPERFECTIONS

ADDITIONAL LIMITED WARRANTY AVAILABLE ON A CASE BY CASE BASIS

TECHNICAL SPECIFICATIONS

SIZE	230.12mm x 1524mm (9.06" x 60")
WEAR LAYER THICKNESS	20MIL
OVERALL THICKNESS	5mm
CORE MATERIAL	STONE PLASTIC COMPOSITE
UNDERLAYMENT	1mm ANTI-MICROBIAL HIGH DENSITY IXPE
EDGE DETAIL	MICRO-BEVELED
FINISH	MINERAL ENHANCED UV COATING
EMBOSSING	ALLOVER
SQ. FT./CARTON	26.41 (2.45m ²)
LIMITED WARRANTY	15 YEARS LIGHT COMMERCIAL, 5 YEARS COMMERCIAL
RATINGS	STC 62 & IIC 68

